


JumpAir Elite area elastic sport parquet system			
<i>Property</i>	<i>Standard</i>	<i>Unit</i>	<i>Result</i>
DESCRIPTION			
JumpAir / sport parquet top layer	Multi layered wooden parquet according to EN 13849; With 3,5 mm hardwood wear layer		
ShockPad Elite / underlay	Impact absorbing sub-construction		
Thickness	EN 13647	mm	39
Weight	-	kg/m ²	11
CLASSIFICATION			
Product specification	Indoor sport parquet system for professional multisport applications. Category A4 according to EN 14904.		
Thermal resistance	EN 12664	m ² K/W	0,38
Reaction to fire	EN 13501	-	Dfl-s1
Formaldehyde content	EN 717-2	-	E1
Pentachlorophenol	-	-	No pentachlorophenol
SPORT PROPERTIES			
Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	59
Vertical deformation	EN 14809	mm	3,2
Ball rebound	EN 12235	%	95
Specular gloss	EN 2813	%	< 30
TECHNICAL CHARACTERISTICS			
Chemical resistance	EN 13442	-	no change
Abrasion resistance (CS10 wheel)	EN ISO 5470-1	mg/1000cycles	< 80
OTHERS			
Limited warranty		5 years	
Appearance, labelling	<input type="checkbox"/> Oak, unique <input type="checkbox"/> Ash, natur		
Dimensions	JumpAir	2250 x 190 x 14 mm	
	ShockPad Elite	2550 x 1125 x 24 mm	